

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
**WO 2004/028416 A1**

(51) International Patent Classification<sup>7</sup>: **A61F 2/68**

(21) International Application Number:  
PCT/US2002/030471

(22) International Filing Date:  
26 September 2002 (26.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(63) Related by continuation (CON) or continuation-in-part  
(CIP) to earlier application:  
US 09/820,895 (CIP)  
Filed on 30 March 2001 (30.03.2001)

(71) Applicants and

(72) Inventors: **TOWNSEND, Barry, W.** [US/US];  
400 Houchin Road, Bakersfield, CA 93304 (US).  
**CLAUDINO, Byron, K.** [US/US]; 9731 Rosedale High-  
way, Bakersfield, CA 93312 (US).


(74) Agents: **SHORE, Ronald, J. et al.**; Antonelli, Terry, Stout  
& Kraus, LLP, Suite 1800, 1300 North Seventeenth Street,  
Arlington, VA 22209 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PROSTHETIC FOOT WITH TUNABLE PERFORMANCE



(57) Abstract: A prosthetic foot (70) incorporates a foot keel (71) and a calf shank (72) connected to the foot keel to form an ankle joint area of the prosthetic foot. The foot keel has forefoot and hindfoot portions and an upwardly arched midfoot portion extending between the forefoot and midfoot portions. The calf shank includes a downward convexly curved lower end in the form of a spiral which is adjustably attached at a portion thereof to the foot keel by way of a coupling element. The calf shank extends upward anteriorly from the spiral to an upstanding upper end thereof. The coupling element includes a stop of a predetermined size to limit dorsiflexion of the calf shank in gait. The calf shank creates an integrated ankle and calf shank with the foot keel which has a variable radii response outcome similar to the disclosed parabola shaped calf shank while being readily covered by a cosmetic covering for the foot, ankle and lower leg.